

Multifunctional descender kit developed for use in situations that require a high resistance to heat, fire and cutting. The descent line is the Blazer 11 mm rope with a para-aramid material sheath that allows for use up to 350°C (melting temperature > 450°C).

The locking cam system uses an innovative design for smooth action on the rope and the absorption of energy from small shocks and dynamic loads with a slight amount of rope slippage. Adjustment is simple and intuitive. To reduce length, simply pull the rope through the device. To increase length, use the trigger for limited tension situations or the lever when the rope is completely loaded.

Multiple certifications for a wide variety of uses: EN 341/2A emergency evacuation device, EN 12841/C rope access descender, EN 353-2 fall arrester, EN 358 work positioning lanyard, EN 795/B anchoring device.

The rope is removable and replaceable.

The Druid Pro Fire is available with fire resistant carrying bag (ref.320201) or without (ref.320202). The bag can be easily fastened to proper loops on the FRX harness.

Spare rope ref.32020101. Spare bag ref.3269.



Ref.	Product name	Weight		Breaking load	Rope diameter		CE				STANDARD
		g	oz		kN	Min - mm	Max - mm	EN 12841/C	EN 358	EN 353-2	EN 795-B
320201	DRUID PRO FIRE 20 m + 2125 + 0995 + BAG	2400	84.7	15	11	11	•	•	•	•	•
320202	DRUID PRO FIRE 20 m + 2125 + 0995 - NO BAG	2020	71.3	15	11	11	•	•	•	•	•



